



## TECHNICAL PARAMETERS

Name		Data
Basic	Operating weight	5720 kg
	Boom length	3000 mm
	Arm length	1550 mm
	Standard bucket	0.23 m³
	Max.Travel speed	2.5/5.0 km/h
	Max.Swing speed	10.5 rpm
	Grade ability	35°(70%)
	Ground pressure	31 kPa
	Max.Traction force	58.3 kN
Engine	Engine model	WP3.2G50E311
	Rated power	36.8 kW/2200 rpm
	Max.Torque	200/1400-1700 N.m/rpm
	Displacement	3.17 L
	Fuel tank	130 L
Hydraulic	Max.Flow(total)	151 L/min
	Max.Working pressure	24.5 MPa
	Max.Pilot pressure	3.7 Mpa
	Max.Arm digging force	28 kN(ISO)
	Max.Bucket digging force	40 kN(ISO)
	Hrdraulic oil tank	80 L
Chassis	Track width	400 mm
	Track shoes number	38( each side)
	Carrier rollers number	1( each side)
	Track rollers number	5( each side)
Electric	System vottage	12 V
	Battery capacity	12 V,100 Ah

## CONFIGURATION

Name	Manufacturer
Engine	Weichai
Main valve	Lonking
Main pump	Lonking
Swing motor	Lonking
Travel motor	Lonking
Electric system	Yongqing

## OPTIONAL

0.1m³ narrow bucket
0.33m³ loading bucket
breaking hammer & pipeline
Quick coupler pipeline
Work warning light
Walking alarm
Top protecting net
Front protecting net
500mm triple grouser shoes
600mm triple grouser shoes
Track rubber block

## PRODUCT FEATURES

Weichai inline 4-cylinder, four-stroke engine with high-pressure common rail electronically controlled fuel injection system
High efficiency dual air and fuel filters
Parallel radiator cooling system
LUDV power balanced hydraulic system
Large LCD monitor and advanced electronic monitoring system
Safe and comfortable cab, ergonomic design
No frame cab glasses to enlarge the visual field
Working device adopts low alloy and high strength structural steel.

# Lonking 龙工

## CDM6060W HYDRAULIC EXCAVATOR

Efficiency Rules the Future



The following blank can be used for notes or comments.

For more information on Lonking products,  
Please contact our local agent:

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd., and may not be used without written permission.  
2020/03

Specifications and design are subject to change without prior notice.  
Machines shown may not include optional accessories.

Lonking (Fu Jian) International Trade Co., Ltd.

**Lonking Holdings Limited**

Add:26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai

Tel: +86-21-3760 2242

E-mail:export@lonking.cn

<http://www.lonkinggroup.com>

OPERATING WEIGHT:	5720kg
ENGINE POWER:	36.8kW
BUCKET CAPACITY:	0.23m³
TRAVEL SPEED:	2.5/5.0km/h